

Exclusively from your Caterpillar® dealer



GEP30-1 (3-Phase)

50 HZ

STANDBY 30.0 kVA / 24.0 kW

PRIME 27.0 kVA / 21.6 kW

60 HZ

STANDBY 34.0 kVA / 27.2 kW

PRIME 30.0 kVA / 24.0 kW

FEATURES

GENERATING SET

- Complete system designed and built at ISO9001 certified facility
- Factory tested to design specifications at full load conditions
- Fully engineered with a range of options and accessories

ENGINE

- Industrial water cooled diesel engine
- Governor, mechanical
- Electrical system, 12 VDC
- Cartridge type fuel and oil filters
- Air filter
- Battery(ies), rack and cables

ALTERNATOR

- Self excited brushless generator
- Insulation system, class H
- Drip proof generator air intake (IP23)
- Electrical design in accordance with BS4999, BS5000, BSEN60034, BSEN61000, IEC60034

CONTROL SYSTEM

- 1001 keystart control panel
- Vibration isolated sheet steel enclosure with hinged lockable door

MOUNTING ARRANGEMENT

- Heavy-duty fabricated steel base with lifting points
- Anti-vibration pads to ensure vibration isolation
- Engine coupled to generator with flexible disc-coupling
- Baseframe incorporates heavy-duty fabricated steel fuel tank, 8 hours running capacity

EXHAUST SYSTEM

- Heavy duty industrial capacity exhaust silencer (approximately 10 dB reduction) supplied loose

COOLING SYSTEM

- Standard ambient temperatures up to 50° C (122° F)
- Fan, fan drive and charging alternator fully guarded
- Antifreeze protection coolant

CIRCUIT BREAKER

- 3-pole miniature circuit-breaker (mcb) < 160 amps and 3-pole molded case circuit breaker (mccb) >= 160 amps
- Vibration isolated sheet steel enclosure with removable cover plate
- Outgoing cable stub-up area directly below circuit breaker

AUTOMATIC VOLTAGE REGULATOR

- Voltage regulation ±0.5 %
- Provides fast recovery from transient load changes

EQUIPMENT FINISH

- All electroplated hardware
- Anticorrosive paint protection
- High gloss polyurethane paint for durability and scuff-resistance

QUALITY STANDARDS

- BS4999, BS5000, BS5514, IEC60034

DOCUMENTATION

- Operation and maintenance manuals provided
- Wiring diagrams included

WARRANTY

- All equipment carries full manufacturer's warranty

5 0 H z	S T A N D B Y	3 0 k V A / 2 4 . 0 k W
	P R I M E	2 7 k V A / 2 1 . 6 k W
6 0 H z	S T A N D B Y	3 4 k V A / 2 7 . 2 k W
	P R I M E	3 0 k V A / 2 4 . 0 k W

OLYMPIAN™

Exclusively from your Caterpillar® dealer

OPTIONAL EQUIPMENT*

Engine	Electronic governor (fully adjustable) Lube oil drain Lube oil drain valve Lube oil drain pump
Generator	Anti-condensation heater
Cooling System	Coolant heater Low coolant temperature alarm Low coolant level shutdown Radiator transition flange Coolant drain
Fuel System	Manual fuel pump Low fuel level shutdown Low fuel level alarm High fuel level alarm Remote fuel systems Manual Bypass Valve
Silencer System — Open Unit	Level 2 silencer with mounting kit (approximately 25 dB reduction) Level 3 silencer with mounting kit (approximately 35 dB reduction) Overhead mounting kit for level 1 silencer Level 1, 2 and 3 silencer installation kits
Enclosures	Sound attenuated (EC) canopy
Handling	Oil field skid Single point lift
Controls	Baseframe mounted terminal box instead of control panel PowerWizard 1.0 panel PowerWizard 2.0 panel
Remote Annunciators	PowerWizard Annunciator
Circuit Breaker	Upgrades from 3-pole to 4-pole breaker
Transfer Switches	TM Series manual load transfer panels ATI Series load transfer panels and bypass switches
Certification	European CE certification (not available on 60 Hz models)

*Some options may not be available on all models.
Not all options are listed.

Consult your Olympian representative for more information

50 Hz	STANDBY	30 kVA	/	24.0 kW
	PRIME	27 kVA	/	21.6 kW
60 Hz	STANDBY	34 kVA	/	27.2 kW
	PRIME	30 kVA	/	24.0 kW

Exclusively from your Caterpillar® dealer

SPECIFICATIONS



ALTERNATOR

Make Olympian
 Model LL1014Q
 Type Self-excited, brushless
 Voltage regulation ±0.5% at steady state from
 no load to full load
 Frequency ±0.8% for constant load from
 no load to full load
 Waveform distortion THD <4%
 Radio interference Compliance with EN61000-6
 Telephone Interference TIF <50, THF <2%
 Overspeed limit 2250 rpm
 Insulation Class H
 Temperature rise Within Class H limits
 Deration Consult factory for available outputs





ENGINE

Manufacturer Perkins
 Model 1103A-33G1
 Type 4-Cycle
 Aspiration Naturally aspirated
 Cylinder configuration In-line 3
 Displacement — L (cu in) 3.3 (201)
 Bore/stroke — mm (in) 105/127 (4.1/5.0)
 Compression ratio 19.25:1
 Engine speed — rpm
 50 Hz 1500
 60 Hz 1800

Piston speed — m/sec (ft/sec)
 50 Hz 6.4 (20.8)
 60 Hz 7.6 (25.0)
 Maximum power at rated rpm — kW (hp)
 Standby
 50 Hz 31.0 (42.0)
 60 Hz 36.5 (49.0)
 Prime
 50 Hz 28.2 (38.0)
 60 Hz 33.1 (44.0)
 BMEP — kPa (psi)
 Standby
 50 Hz 752 (109)
 60 Hz 738 (107)
 Prime
 50 Hz 684 (99.2)
 60 Hz 669 (97.0)
 Regenerative power — kW (hp)
 50 Hz 7.0 (9.4)
 60 Hz 9.0 (12.1)
 Governor
 Type Mechanical
 Class ISO 8528 G2

GENERATOR SET DIMENSIONS AND WEIGHTS



Model	Length mm (in)	Width mm (in)	Height mm (in)	Weight* kg (lb)
GEP30-1	1770 (69.7)	714 (28.1)	1368 (53.9)	800 (1764)

Note:- General configuration not to be used for installation. See general dimension drawings for detail.

*Includes oil and coolant

Consult your Olympian representative for more information

50 Hz	STANDBY	30 kVA	/	24.0 kW
	PRIME	27 kVA	/	21.6 kW
60 Hz	STANDBY	34 kVA	/	27.2 kW
	PRIME	30 kVA	/	24.0 kW

OLYMPIAN™

Exclusively from your Caterpillar® dealer

GEP30-1 (3-Phase)

Generating Set Technical Data		50 Hz		60 Hz	
		Standby	Prime	Standby	Prime
Package Performance Power rating	kVA (kW)	30.0 (24.0)	27.0 (21.6)	34.0 (27.2)	30.0 (24.0)
Lubricating System Type: Oil pump & lubrication sump Oil filter: Spin-on, full flow Oil cooler: Water Oil type required: API G4 15W-40 Total lube system capacity Oil pan capacity	L (U.S. Gal) L (U.S. Gal)	8.3 (2.2) 7.8 (2.1)		8.3 (2.2) 7.8 (2.1)	
Fuel System Fuel Tank Capacity Generator set fuel consumption** 100% load 75% load 50% load	L (U.S. Gal) L/hr (U.S. g/hr) L/hr (U.S. g/hr) L/hr (U.S. g/hr)	144 (38.0) 6.9 (1.8) 5.2 (1.4) 3.8 (1.0)	6.2 (1.6) 4.8 (1.3) 3.6 (1.0)	144 (38.0) 8.1 (2.1) 6.3 (1.7) 4.7 (1.2)	7.2 (1.9) 5.7 (1.5) 4.4 (1.2)
Engine Electrical System Voltage/ground: 12 vDC/negative Battery charging alternator ampere rating	amps	65		65	
Cooling System Water pump type: Centrifugal Cooling system capacity Maximum coolant static head Coolant flow rate Minimum temperature to engine Temperature rise across engine Heat rejected to coolant at rated power Total heat radiated to room at rated power Radiator fan load	L (U.S. Gal) m H ₂ O (ft H ₂ O) L/hr (U.S. gal/hr) °C (°F) °C (°F) kW (Btu/min) kW (Btu/min) kW (hp)	10.2 (2.7) 10.2 (33.5) 7530 (1989) 70.0 (158) 1.9 (3.4) 13.8 (785) 8.6 (489) 0.3 (0.4)	12.1 (688) 7.4 (421)	10.2 (2.7) 10.2 (33.5) 9060 (2393) 70.0 (158) 1.9 (3.4) 19.4 (1103) 8.8 (500) 0.5 (0.7)	16.8 (955) 7.5 (427)
Air Requirements Combustion air flow Maximum air cleaner restriction Radiator cooling air External restriction to cooling airflow Generator cooling air	m ³ /min (cfm) kPa (in H ₂ O) m ³ /min (cfm) Pa (in H ₂ O) m ³ /min (cfm)	2.5 (88.0) 6.5 (26.1) 69.6 (2458) 120 (0.5) 9.0 (318)	2.5 (88.0) 6.5 (26.1) 69.6 (2458) 120 (0.5) 9.0 (318)	2.9 (102) 6.5 (26.1) 90.6 (3200) 120 (0.5) 10.8 (381)	2.8 (99.0) 6.5 (26.1) 90.6 (3200) 120 (0.5) 10.8 (381)
Exhaust System Maximum allowable backpressure Exhaust flow at rated power Exhaust temperature at rated power (dry exhaust)	kPa (in Hg) m ³ /min (cfm) °C (°F)	15.0 (4.4) 5.2 (184) 472 (882)	4.2 (148) 4.2 (148) 454 (849)	15.0 (4.4) 6.3 (222) 501 (934)	5.1 (180) 5.1 (180) 492 (918)
Generating Set Noise Rating* (without attenuation) at 1 m (3.28 ft)	dBA	89.4		91.8	

*dBA levels are for guidance only

**Fuel consumption data at indicated load with diesel fuel with a specific gravity of 0.85 and conforming to BS2869:1998 Class A2.

Generator Technical Data	50 Hz				60 Hz				
	415/240V	400/230V 230/115V 200/115V	380/220V 220/110V	220/127V	480/277V 240/139V	440/254V 220/127V	240/120V 208/120V	230/115V	380/220V 220/110V
Motor Starting Capability: Self Excited (kVA)	62.0	58.0	53.0	68.0	67.0	58.0	53.0	50.0	45.0
Full Load Efficiency									
Standby %	88.4	88.3	88.0	88.4	89.3	89.0	88.6	88.1	87.5
Prime %	88.8	88.8	88.6	88.5	89.7	89.5	89.1	88.8	88.3
Reactances (per unit)	Xd	2.02	2.18	2.41	1.71	2.05	2.44	2.73	2.96
Saturated	X'd	0.11	0.12	0.13	0.09	0.11	0.13	0.15	0.16
Reactances are shown	X"d	0.056	0.060	0.066	0.047	0.057	0.067	0.075	0.082
applicable to the	Xq	1.01	1.09	1.20	0.85	1.03	1.22	1.37	1.48
standby rating	X"q	0.078	0.084	0.093	0.066	0.080	0.095	0.106	0.115
	X2	0.068	0.073	0.081	0.057	0.069	0.082	0.092	0.099
	X0	0.005	0.006	0.006	0.004	0.005	0.006	0.007	0.008
Time Constants:	t'd 25 ms		t" 2.5 ms		t'do 452 ms			ta 4 ms	

Consult your Olympian representative for more information

5 0 H z S T A N D B Y 3 0 k V A / 2 4 . 0 k W
 P R I M E 2 7 k V A / 2 1 . 6 k W
 6 0 H z S T A N D B Y 3 4 k V A / 2 7 . 2 k W
 P R I M E 3 0 k V A / 2 4 . 0 k W

Exclusively from your Caterpillar® dealer

RATINGS AT AVAILABLE VOLTAGES

50 Hz					
Voltage Code	Voltage	Standby		Prime	
		kVA	kW	kVA	kW
VOPT502	415/240	30.0	24.0	27.0	21.6
VOPT503	400/230	30.0	24.0	27.0	21.6
VOPT504	380/220	30.0	24.0	27.0	21.6
VOPT506	230/115	30.0	24.0	27.0	21.6
VOPT507	220/127	28.0	22.4	25.0	20.0
VOPT508	220/110	30.0	24.0	27.0	21.6
VOPT510	200/115	30.0	24.0	27.0	21.6

60 Hz					
Voltage Code	Voltage	Standby		Prime	
		kVA	kW	kVA	kW
VOPT601	480/277	34.0	27.2	30.0	24.0
VOPT603	440/254	34.0	27.2	30.0	24.0
VOPT605	380/220	33.9	27.1	30.0	24.0
VOPT606	240/120	34.0	27.2	30.0	24.0
VOPT607	230/115	34.0	27.2	30.0	24.0
VOPT608	220/127	34.0	27.2	30.0	24.0
VOPT609	220/110	33.9	27.1	30.0	24.0
VOPT610	208/120	34.0	27.2	30.0	24.0
VOPT611	240/139	34.0	27.2	30.0	24.0

Ratings at 27° C (80° F), 152.4 m (500 ft), 60% humidity, 0.8 pf

RATING DEFINITIONS

STANDBY

These ratings are applicable for supplying continuous electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings. When used at standby rating the alternator will be peak continuous rated (as defined in ISO8528-3).

PRIME POWER

These ratings are applicable for supplying continuous power (at variable load) in lieu of commercially purchased power. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours.

Consult your Olympian representative for more information

50 Hz	STANDBY	30 kVA / 24.0 kW
	PRIME	27 kVA / 21.6 kW
60 Hz	STANDBY	34 kVA / 27.2 kW
	PRIME	30 kVA / 24.0 kW

OLYMPIAN™

Exclusively from your Caterpillar® dealer